

NON-NUCLEAR ASPHALT DENSITY GAUGE EDG-A

- New status bar feature, displays GPS status, data save status, available battery voltage, low battery status and date and time
- Measures density in common units (Kg./M3), and can measure the asphalt temperature
- New data management feature, you can store 4000 readings on the internal data logger, quickly access, download or delete your project data
- Ability to download files from the EDG-A via USB drive
- Light weight and easy to use, 24 hours of portable operation
- Fast, reliable, accurate and repeatable readings in real time, user friendly, cost effective
- Non-Nuclear means no badges, licenses or storage and transport concerns





NON-NUCLEAR ASPHALT DENSITY GAUGE EDG-A



OPERATIONAL SPECIFICATIONS

MODES

Single: Reading time less than five (5) seconds. Stores Data. Average: Averages five (5) readings and stores data including date and time. Stores thousands of records. Continuous: Instantaneous density readings.

FUNCTIONS

Density, % Compaction Integrated Temperature Sensing: Real time temperature display 0 $^{\circ}\mathrm{C}$ to 350 $^{\circ}\mathrm{C}$

CALIBRATION MODES

Normal: Correlation offset to cores.

MEASUREMENT SPECIFICATIONS

Sensing Area: 11 in. (27.9cm) diameter base allows optimum measurement on fine and coarse material types.

Measurement Depth: 110mm

Measurement Display: Density, % Compaction, Surface Temperature, Mix Name & Project Name

MECHANICAL SPECIFICATIONS

Shipping Weight w/Case: 9.00kg

Shipping Dimensions: 490 × 220 × 390mm

ELECTRICAL SPECIFICATIONS

MICROPROCESSOR CONTROLLED

Battery: 2.5 Amp-hr NiMH, 12V

Recharge Time: 4 hours

Battery charger: 12V Universal AC charge

Computer Ports: 1 USB Port

WARRANTY

Standard: 12 month

Optional Extended Warranty: Customer CarePlan available

OPERATIONAL FEATURES

Status Bar: Displays GPS status, Data Save status, battery voltage, low battery and date and time

Project Details: Stores up to 10 projects with details

Mix Details: Stores up to 20 mixes, details include (MTD, Mix Name, Stone Size, Depth, Offset, Operator Name)

Data Logging: When enabled, stores all measurements taken in single or average modes, (Status Bar Icon)

Reports: Easily download data to be imported into Excel GPS Control: When activated will display latitude and longitude positions, number of satellites the gauge is connected to as well as the UTC date and time, also available in UTM format. GPS information will store with each measurement when Data Save and GPS feature is enabled, (Status Bar Icon)

Update Software: One touch upload of new software using a USB memory stick

Data Management: Quickly access, download or delete your project data

Set Time & Date: Quick time and date setup, MM/D-D/YY and DD/MM/YY formats

Units: Interchangeable settings for Density (kg/m3, lb/ft3), Temp ($^{\circ}$ C, $^{\circ}$ F), Depth (in, mm) and Stone Size (in, mm)

Calculator: Built in four function calculator

Enhanced Customer Support: Diagnostic screen to aid in factory support

User Programmable Target Density: Used for calculating % compaction

EDG-A COMPLIES WITH





D7113-05

T 343-12

SINCE 2006

ZHUOZHOU TIANPENG INSTRUMENT MANUFACTURING CO., LTD. Website: www.testmould.com Tel:+86-312-3852880