

DYNAMIC CONE PENETROMETER K-100

STANDARD: ASTM D 6951-03

The K-100 Standard Kit measures the shear strength of soil with a CBR between 0.5-100. Affordably priced, this kit is for local engineers and geotech firms. With it the user can produce CBR value profiles in the field. It comes with a 30" drive rod (actual penetration depth 28 1/4"), 25 disposable cones and a cone adapter for fast and easy extraction of the instrument from hard soil. The stainless steel dual mass hammer and carrying case are included. Additional disposable cones, cone adapters, and hardened points are available. One year warrantee against any manufacturing defects.



COMPRISES

K100	Upper assembly (Stainless Steel) includes:	K012	DCP User's Manual
• K103	• Quick-Connect Upper Rod	K450	Pins with Clips, 2 per package
• K102	• Handle	K500	Vertical Scale, 40"
• K200	• Dual Mass Hammer	K510	Foot for Vertical Scale
K1330	Drive Rod 30" Stainless Steel with end cap	K530	Upper Attachment for Vertical Scale
K420	Hex Key, 1/4", "Allen" Wrench Type	K700	Reusable Hardened Point
K430	3-in-ONE Oil	K800	Adapter for Disposable Cones
K445	Wrenches 9/16", open end, black	K900	Disposable Cones, Pkg of 25
K011	CD of DCP User's Manual & Excel® Template	P-1720	Alloy Aluminum Carrying Case

ACCESSORIES AND SPARE PARTS (need to be ordered separately)

K133775	37.75" Drive Rod (Penetration to 35.75") (Stainless Steel) with end cap	K1348	Stainless Steel 48" Drive Rod
K1312	12" Drive Rod for use with 24" Extension Rods	K1348S	Extra Strong 48" Drive Rod
K1724	Extension Rod 24" for use with 12" Drive Rod in weak soil	K133775S	Extra Strong 37.75" Drive Rod



SINCE 2006

ZHUOZHOU TIANPENG INSTRUMENT MANUFACTURING CO., LTD.
 Website: www.testmould.com Tel: +86-312-3852880