

# COMPRESSION TESTING MACHINE DYE-2000

**STANDARD: EN 12596, ASTM D445, ASTM D2171**

It is used for cleaning asphalt and polymers adhered to the capillary viscometers and vacuum decompression capillary viscometer, and is also suitable for cleaning asphalt and polymers on the RTFOT sample bottles.



## FEATURES

- It can clean 3 RTFOT sample bottles or 6 capillary viscometers or 6 vacuum decompression capillary viscometers each time.
- Residual asphalt removal effect is good.
- The cleaning time is short, and the cleaning can be completed in 20-60 minutes.
- Aerospace heat insulation material is used, which has good heat insulation performance and is safe to use.
- The temperature is controlled by a temperature control meter, and the operation is simple.
- Condensation method: circulating water.

## APPLICATION

Capillary viscometers

Vacuum decompression capillary viscometer

RTFOT sample bottles

## TECHNICAL SPECIFICATIONS

Working temperature range	90~160°C
Heating bath temperature	200°C
Working space size	Ø250 mm
Main unit power supply	220V±10V 50Hz
Dimensions	450 × 450 × 750 (mm)
Weight	20 kg
Ambient temperature	-5°C ~50°C
Ambient humidity	<80%
Refrigeration capacity	50 W/°C
Chiller power	1 kW
Chiller dimensions	260 mm × 670 mm × 400 mm



**SINCE 2006**

**ZHUZHOU TIANPENG INSTRUMENT MANUFACTURING CO., LTD.**  
 Website: [www.testmould.com](http://www.testmould.com) Tel: +86-312-3852880